

COMMUNICATIONS RESOURCE AVAILABILITY WORKSHEET					Frequency Band			Description	
					Amateur Radio			Livingston Co. MO	
Channel Configuration	Channel Name/Trunked Radio System Talkgroup	Eligible Users	RX Freq N or W	RX Tone/NAC	TX Freq N or W	Tx Tone/NAC	Mode A, D or M	Remarks	
Repeater	LIV Co. ARES NC Mo SKYWarn	Amateur	147.225 W (+)	CSQ	147.825 W	CSQ	A	LIV- Chillicothe, KOMPT	
Simplex	Repeater failure simplex	Amateur	147.225 W	CSQ	147.225 W	CSQ	A	LIV- Chillicothe, KOMPT	
APRS	APRS Digipeater	Amateur	144.390 W	CSQ	144.390 W	CSQ	D	LIV- Chillicothe, KC0NOX	
Repeater	CRIS net access	Amateur	444.400 W (+)	100	449.400 W	100	A	LIV- Chillicothe, KB0YAS	

The convention calls for frequency lists to show four digits after the decimal place, followed by either an "N" or a "W", depending on whether the frequency is narrow or wide band. Mode refers to either "A" or "D" indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.